



EnergyMetering

RNK-RP-N

Volumetric rotary-piston
meter with protected dial

retrofitable with pulser



ZENNER
All that counts.

RNK-RP-N

Volumetric rotary-piston meter for cold potable water with protected dial and brass body





Our series of RNK-RP volumetric piston meters with protected dial are an improvement of the classical RTK. The millionfold proved and high-precise measuring insert in combination with the rugged casing performs perfectly the measurement of potable water. A very low starting flow and reliable performance are

its main features. The protected roller counter is reliably readable even under demanding climatic conditions. Filter is including. The construction principle of the RNK-RP-N with direct transmission from the measuring chamber to the counter ensures by standard protection against magnetic or other manipulation attempts or interference.

The optional internal check valve ensures additional protection and backflow prevention.

Performance characteristics in overview

- Rugged and intelligently conceived
- Counter with protected rollers
- Body made from high-quality brass
- Working temperature 30°C, security up to 50°C
- Operating pressure PN16
- Display range 0,02 l to 9.999 m³
- Proven accuracy in any installation position
- Optional with integrated tamperproof check valve
- Retrofitable with pulser 0,5 l/pulse (DN 40 5l/pulse)
- Other sizes of volumetric meters up to DN 40 available on request
- According to ISO 4046 and MID 2004/22/EC



RNK-RP-N- DN20

RNK-RP-N- DN15

Technical Data		RNK-RP-N- DN15					RNK-RP-N- DN20	
Nominal width	DN	mm	15	20	25	32	40	
Nominal flow	Q3	m ³ /h	2,5	4	6,3	10	16	
Metrological class (*)	Q3/Q1		160	200	200	200	200	
Maximum flow	Q4	m ³ /h	3,125	5	7,875	12,5	20	
Minimum flow	Q1	L/h	16	20	32	50	80	
Length	L	mm	110/115/165	165/190	260	260	300	
Width	B	mm	88	100	117	145	179	
Thread meter			G3/4B	G1B	G1 1/4B	G1 1/2B	G2B	
Weight ca.		kg	0,79/0,80/0,95	1,1/1,2	2,5	3,6	5,9	

(*) Standard Ratio R160

ZENNER International GmbH & Co. KG

Römerstadt 6
D-66121 Saarbrücken

Telephone +49 681 99 676-30
Telefax +49 681 99 676-3100

E-Mail info@zenner.com
Internet www.zenner.com